



**SYNTHETIC BLEND PASSENGER CAR MOTOR OILS**  
**5W-20, 5W-30, 10W-30**  
**API - SN, ILSAC GF-5**

Technical Data

LUBRISTRONG 5W-20, 5W-30, & 10W-30 API - SN, ILSAC GF-5 SYNTHETIC BLEND PASSENGER CAR MOTOR OILS are multi-grade parasynthetic lubricants designed for use in modern fuel injected gasoline engines. LUBRISTRONG 5W-20, 5W-30, & 10W-30 API - SN, ILSAC GF-5 SYNTHETIC BLEND PASSENGER CAR MOTOR OILS are formulated with synthetic and type II paraffinic base oils and a special additive package designed for superior protection against wear, corrosion, oxidation and varnish. Furthermore, a unique detergent additive prevents sludge or carbon deposits especially in extreme heat or pressure conditions. With superior anti-shear properties and high-viscosity index type II paraffinic and synthetic base stocks, LUBRISTRONG 5W-20, 5W-30, & 10W-30 API - SN, ILSAC GF-5 SYNTHETIC BLEND PASSENGER CAR MOTOR OILS enhance engine performance, extend oil life, ease cold-starts, and eliminate viscosity breakdown. These oils exceed the performance requirements of the American Petroleum's Institute's SN service category as well as ILSAC service category GF-5.

SPECIFICATIONS

PARAMETER	5W-20	5W-30	10W-30
Appearance	Amber,	Bright,	Free & Clear
Viscosity cSt @ 40°C	50.8	77.1	81.4
Viscosity cSt @ 100°C	7.8	10.6	10.8
Pour Point, °F	-34	-35	-26
Flash Point, °F	406	402	405
Viscosity Index	121	124	119

Exceeds Specification Requirements:

API - SN	API - SM	API - SL	API - SJ
ILSAC - GF-5	ILSAC GF-4	ILSAC GF-3	
GM 6094M	Ford WSSM2C945-A (5W-20)	Ford WSS-M2C946-A (5W-30)	
Chrysler MS-6395	Toyota	Honda	



*Made in USA*